



Decorative Lighting

APS Twinkle Light

Code	Color	Protection	Voltage	LED	Length	
OLE LD06-TW-100	White	IP40	240V	100	5M	
OLE LD06-TW-060	Blue (stable)	IP44	240V	60	6M	Transparent wires & white rectifier PC
OLE LD06-TW-060	White (stable)	IP44	240V	60	6M	Transparent wires & white rectifier PC
OLE LD06-TW-100	Blue	IP44	240V	100	5M	Black wire w/o cont.
OLE LD06-TW-100	Red	IP44	240V	100	5M	Black wire w/o cont.
OLE LD06-TW-100	White	IP44	240V	100	5M	Black wire w/o cont.
OLE LD06-TW-100	Yellow	IP44	240V	100	5M	Black wire w/o cont.
OLE LD06-TW-100	Red	IP44	240V	100	5M	50cm Long power w/o cont. (w.wire)
OLE LD06-TW-120	Blue	IP44	240V	120	6M	
OLE LD06-TW-120	Green	IP44	240V	120	6M	
OLE LD06-TW-100	White	IP65	240V	100	5M	T. cable 0.2mm 4 stable+1 flashing
OLE LD06-TW-120	Yellow	IP65	240V	120	6M	Black cable with controller (waterflow)
OLE LD06-TW-B100	Purple	IP65	260V	100	5M	Black wire connectable max 5 set
OLE LD06-TW-B100	Warm white	IP65	260V	100	5M	Black wire connectable max 5 set
OLE LD06-TW-BSR-RC	Blue	IP65	240V	100	5M	Black rubber wire, non connectable, 1M power con.
OLE LD06-TW-BSR-RC	White	IP65	240V	100	5M	Black rubber wire, non connectable, 1M power con.
OLE LD06-TW-BSR-RC	Warm White	IP65	240V	100	5M	Black rubber wire, non connectable, 1M power con.
OLE LD06-TW-BSR-RC	White	IP65	260V	120	6M	Black rubber wire (0.3MM copper), non connectable
OLE LD06-TW-BSR-RC	Warm White	IP65	260V	120	6M	Black rubber wire (0.3MM copper), non connectable
OLE LD06-TW-BSR-RC	Blue	IP65	260V	120	3M	Black rubber wire (0.3MM copper), non connectable
OLE LD06-TW-BSR-RC	White	IP65	260V	120	3M	Black rubber wire (0.3MM copper), non connectable
OLE LD06-TW-BSR-RC	Warm White	IP65	260V	120	3M	Black rubber wire (0.3MM copper), non connectable
OLE LD06-TW-120	Yellow	IP66	240V	120	6M	Black cable
OLE LD06-TW-120	Blue	IP66	240V	120	6M	Black cable

Dimension

